CITY OF FOSTER CITY

ADDENDUM NO. ONE (1) TO THE PROJECT DOCUMENTS

FOR CIP 716 – STREET REHABILITATION AND PARK PATHWAY RESTORATION

Bid Submittal Due Date: Wednesday, June 12, 2024 at 2:00pm

Notice is hereby given that the following revisions, additions, and/or deletions are hereby made a part of, and incorporated into the project documents for CIP 716 – Street Rehabilitation and Park Pathway Restoration.

Bidders shall acknowledge the receipt of this Addendum on the Bid Form (00 4113). Failure to do so may render Bidder's Bid non-responsive.

The following changes, additions or deletions shall be made to the following documents as indicated and shall be part thereof as if originally specified and/or shown. All other terms and conditions remain unchanged.

Construction Services Project Manual:

1. Bid Form (00 4113 – 5)

Replace page 00 4113-5 in its entirety with the attached page.

2. Bid Form (004113 - 7)

Replace 11. Pavers with the following:

- 11. Pavers. Shall be measured and paid for by the square foot, which includes, but is not limited to furnishing of all labor, material, and services required to properly and safely complete all work related to the "Pavers" including, but not limited to the removal of existing pavers, disposal of material, new pavers, and clean-up by power washing in conformance with Foster City Standard Specification Section 02 3400, Standard Details, and as shown on the plans and specified herein.
- 3. DIVISION 2 TECHNICAL SPECIFICATIONS, SECTION 02 3400, BITUMEN-SET CONCRETE PAVERS (02 3400 3)

Replace PART 2 PRODUCTS – 2.01 Concrete Pavers with the following:

A. Manufacturer: Endicott

1. Contact: 402-729-3315

- B. Concrete Paver Units, including the following:
 - 1. Paver Type: INVISI-LUG 4" x 8" with wirecut finish

- (a) Material Standard: Comply with ASTM C936.
- (b) Color: Medium Ironspot #46
- (c) Color Pigment Material Standard: Comply with ASTM C979.
- (d) Size: 4 x 8 x 2-1/4 inches (102 x 203 x 57 mm)
- (e) Average Compressive Strength (ASTM C140): 8000 psi (55 MPa) with no individual unit under 7200 psi (50 MPa).
- (f) Average Water Absorption (ASTM C140): 5% with no unit greater than 7%.
- (g) Freeze/Thaw Resistance (ASTM C1645): 28 freeze-thaw cycles
- (h) with no greater loss than 225 g/m2 of paver surface area or no greater loss than 500 g/m2 of paver surface area after 49 freeze-thaw cycles when immersed in a 3% saline solution. Use -15 deg. C as the lowest test temperature for applications subject to deicers. Freeze-thaw testing requirements shall be waived for applications not exposed to freezing conditions.

Approved By: Imozym	06/06/2024
Andrew Brozyna, P.E. Director of Public Works	Date

66	Traffic Control	1	LS		
67	Erosion Control	1	LS		
68	Install Thermoplastic Type I Arrow	3	EA		
69	Install Thermoplastic Type VII (R) Arrow	2	EA		
70	Install Thermoplastic Type IV (L) Arrow	14	EA		
71	Install Thermoplastic Type IV (R) Arrow	12	EA		
72	Install Thermoplastic Yield Line	2	EA		
73	Install 12" Wide Thermoplastic Crosswalk	536	LF		
74	Install 12" Wide Stop Limit Line	185	LF		
75	Install Detail 9 – Thermoplastic 6" Dashed White Lane Line	6,370	LF		
76	Install Detail 27B – Thermoplastic White Edge Line	2,085	LF		
77	Install Detail 29 – Thermoplastic Median Island Double Yellow Lane Line	115	LF		
78	Install Detail 37B – Thermoplastic Lane Drop at Intersections	560	LF		
79	Install Detail 38 – Thermoplastic White Channelizing Line	1,720	LF		
80	Install Detail 40 – Thermoplastic 6" White Lane Line Extension Through Intersection	125	LF		
81	Install Blue Raised Reflective Hydrant Pavement Marker	2	EA		
82	Furnish and Install New Sign on Existing Pole/Electrolier	45	EA		
				TOTAL BID PRICE	\$

Total Base Bid and Alternate No. 1 and No. 2 Bid Price:

(Indicate Total Base Bid and Alternate No. 1 and No. 2 Bid Price in Words)

(Indicate Alternate No. 2 Bid Price in Words)

Base Bid Items:

Total Alternate No. 2 Bid Price:

- 1. **Demolish Curb and Gutter.** Shall be measured and paid for on a linear foot basis, which includes, but is not limited to furnishing of all labor, material, and services required for saw cutting, removal, and disposal of the existing curb and gutter as shown on the plans and specified herein.
- 2. **Demolish Median Nose.** Shall be measured and paid for on a square foot basis, which includes, but is not limited to furnishing of all labor, material, and services required for saw cutting, removal, and disposal of the existing median nose as shown on the plans and specified herein.
- 3. **2.5" Grind and 2.5" Asphalt Concrete Overlay**. Shall be measured and paid for by the square foot, which includes, but is not limited to furnishing of all labor, material, and services required to properly and safely complete all work related to the "2.5" Grind and 2.5" Asphalt Concrete Overlay" in conformance with Foster City Standard Specifications, Standard Details, as shown on